

COLOUR | GINGER SELECT


Wood species | Oak

Grade | 1 Natur

Constructions | 3-layer T&G Engineered Flooring

Size | 19,05x190x2000...2100 mm (3/4"x7 1/2"x6 9/16"...7") Finish | UV-Oil

CONSTRUCTION : 3-LAYER T&G ENGINEERED FLOORING

DIMENSIONS:		 Solid wood lamella 3,2 mm Birch middle core 12,75 mm Solid wood lamella 3,1 mm Cork compensators	PACKAGING:	BOX	PALLET
Thickness	19,05 mm (3/4")		Content:	1,97m ²	40 (78,8 m ²)
Width	190 mm (7 1/2")		Weight	25 kg	1003 kg
Length	2000...2100 (6 9/16"...7")		H x W x L	100 x 225 x 2165	1134 x 905 x 2165 mm
Average length	1.73 m (5 11/16')		Content:	mm 21,197 sq.ft.	847,888 sq.ft.
Microbevel	0,5 mm		Weight	55 lb	2207 lb
Joint type	(T&G)		H x W x L	4" x 9" x 86"	46" x 33" x 86"

DEVIATIONS :

Deviation on Thickness	± 0,2 mm	EN 13489 ГОСТ 862.3
Deviation on Width	± 0,2 mm	
Height Difference	≤ 0,2 % of width	
Cup	≤ 0,2 % of plank width	
Spring	≤ 0,1 % of length	EN 13489
Bow	≤ 0,5 % of length	

CHARACTERISTICS :

Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,118 m ² ·K/W	
Thermal conductivity	0,161 W/(m·K)	
Structural warranty	Lifetime	

INSTALLATION :



Glue down over concrete, plywood or wooden sub floor or nail down over wooden sub floor. Applicable above, on and below ground level. Suitable for installation over radiant heating systems.

STORAGE AND USAGE :



— Air humidity 40% – 65%
— Temperature +18 °C – +22 °C

FINISH : UV-OIL

DESCRIPTION:

Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores, wire brushed
Sheen	Silk matte 3 - 10 GU/60°
Finish warranty	-

CLASSIFICATION SURFACE CHARACTERISTICS :

Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438
Slip resistance	50 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

MAINTENANCE AND CARE CONDITIONS :

Maintenance of hardwood floors with Silk Oil finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

GRADE : 1 NATUR

DESCRIPTION:		DESCRIPTION	
Sound sapwood	Permitted non-contrasting up to 25% and contrasting up to 5% of the plank area	Bark pocket	Permitted up to 50mm in length, up to 5 mm in width, filled
Colour variation	Moderate variation allowed	Pith	Permitted
Knot	Permitted up to 35 mm, filled	Slope of grain	Permitted
Checks	Permitted narrow, filled	Medullary ray	Permitted